Common Committee

Vidyasagar Group of Colleges 39, Sankar Ghosh Lane Kolkata-700006

TENDER NOTICE FOR REPAIRING OF PHYSICS LABORATORY OF VIDYASAGAR GROUP OF COLLEGES

Tender No: VGC/REPAIR/2023 -1 Date: 10.10.2023

Quotations are invited in sealed cover for the repairing work of Physics Laboratory of Vidyasagar Group of Colleges (old building) 39, Sankar Ghosh Lane Kolkata-700006 as per Annexure from established contractors with proven track record.

Vendors may visit the actual site during office hours i.e 11 am to 4p.m(Contact :9123318397)

Time limit of completion of the work 30 days after issuing of work order.

Interested vendors are requested to submit tender in sealed envelope containing quotation, copy of trade license, GST registration certificate, PAN card and Credentials(if any) addressing to the Convener, Common Committee, Vidyasagar Group of Colleges. The Common Committee of Vidyasagar Group of Colleges will not be liable for late receiving of any quotation. The Common Committee of Vidyasagar Group of Colleges has a right to reject any quotation without assigning any reason and the decision will be binding all.

Important Notes:

1. Date of Publication of Tender : 10.10.2023

2. Time for Submission : 11.00 am to 4.00 pm (except Holidays)

3. Last date for submission : 17.10.2023 upto 2.00pm

4. Place of Submission : Tender box placed at the first floor in front of

room no. 9 of Vidyasagar College (old building)

39, Sankar Ghosh Lane Kolkata-700006

5. Opening of Tender : 17.10.2023 at 2.15 pm

Sd/-Convener Common Committee Vidyasagar Group of Colleges

Annexure

S1. No.	Description of Items	Unit	Qnty.	Rate (Rs.)	Amount (Rs.)
1	DISMANTLING WORK				
1.1	Stripping off worn out plaster (outside and inside) and raking out joints of walls, ceiling etc. upto any height and in any floor including removing rubbish and stacking any where within the compound as directed by EIC.	Sq.M	90.00		
1.2	(a) Applying 2 coats of bonding agent with synthetic multi functional rubber emulsion having adhesive and water proofing properties by mixing with water in proportion (1 bonding agent : 4 water : 6 cement) as per Manufacturer's specification	Sq.M	90.00		
1.3	Dismantling R.C. floor, roof, beams etc. including cutting rods and removing rubbish as directed within a lead of 75 m. including stacking of steel bars.	Cu.M	0.00		
1.4	Dismantling all types of masonry excepting cement concrete plain or reinforced, stacking serviceable materials at site and removing rubbish as directed within a lead of 75 m.	Cu.M	2.00		
1.5	Removal of rubbish,earth etc. from the working site and disposal of the same beyond the compound, in conformity with the Municipal / Corporation Rules for such disposal, loading into truck and cleaning the site in all respect as per direction of Engineer in charge	Cum	25.00		

2	CIVIL WORK			
2.1	Supplying, fitting and fixing boiling water proof ply conforming to IS: 710-1977 bonded with phenol formaldehyde synthetic resin conforming to IS: 848-1974 of approved make and brand fitted and fixed as per design as per approval and direction of Engineer-in-Charge. [excluding the cost of supporting frame work and teak wood batten/Lipping]	Sqm	12.00	
2.2	125 mm. thick brick work with 1st class bricks in cement mortar (1:4) in ground floor.	Sqm	0.00	
2.3	Making one set of scaffolding only for replacing glass panels, painting, uprooting plant and another repairing works of building and S & P works for external works only with 10 cm. dia bamboo as main posts at the rate of 1 metre centre to centre and 7.5 cm. dia bamboo ties @ 0.75 metre apart fitting and fixing with necessary coir, nails etc. as per direction of the Engineer-incharge.			
	a) 3.90 metre height	Each	6	
	b) Extra for additional 3.6 height or part thereof	Each	12	
2.4	Plaster (to wall, floor, ceiling etc.) with sand and cement mortar including rounding off or chamfering corners as directed and raking out joints, including throating, nosing and drip course, scaffolding/staging where necessary (Excluding cost of chipping over concrete surface)			
	(i) With 1:6 cement mortar (a) 20 mm. thick plaster	Sqm	100.00	
	(ii) With 1:3 cement mortar (b) 10 mm. thick plaster	Sqm	20.00	

2.5	Cleaning the exposed reinforcement preferably upto full diameter by wire brush, applying two coats of polymer based rust removing compound left for 24 hours, removing the coating and then applying two (2) coats of polymer modified anti corrosive protective coating formulated to inhibit the corrosion of reinforcement as per manufacturer's specification]	Sqm	8.00			
2.6	Ordinary Cement concrete (mix 1:2:4) with graded stone chips (6mm nominal size) excluding shuttering and reinforcement, if any, in gound floor as per relevant IS codes.	Cum	1.00			
2.7	Applying epoxy based reactive joining agent for joining the old concrete with fresh concrete to be applied within manufacturer's specified time as per manufacturers specification. (0.4 Kg / m² of concrete surface).	Sq.M	30.00			
2.8	Supplying best indian sheet glass panes set in puttty and fitted and fixed with nails and putty complete. 3mm thick (weighing 7.4kg/sqm).	Sqm	5.00			
2.9	Supplying labours for shifting furnitures etc.	each	10.00			
				TOTAL		
	GST @ 18%	T		Ţ		
			Grand '	and Total:		
	(Rupees					
	Date:	Signature of the Contractor				
	Place:					