

**Common Committee**  
Vidyasagar Group of Colleges  
39, Sankar Ghosh Lane  
Kolkata-700006

**TENDER NOTICE FOR RENOVATION OF PHYSICS LAB, GENTS AND LADIES  
TOILET AT VIDYASAGAR GROUP OF COLLEGES**

Tender No: VGC/RENOV/2023 -1

Date: 10.10.2023

Quotations are invited in sealed cover for Renovation of Physics lab, gents and ladies toilet at Vidyasagar Group of Colleges (old building) 39, Sankar Ghosh Lane Kolkata-700006 as per Annexure from established contractors with proven track record.

Vendors may visit the actual site during office hours i.e 11 am to 4p.m(Contact :9123318397)

Time limit of completion of the work 30 days after issuing of work order.

Interested vendors are requested to submit tender in sealed envelope containing quotation, copy of trade license, GST registration certificate, PAN card and Credentials(if any) *addressing to the*Convener, Common Committee, Vidyasagar Group of Colleges.The Common Committee of Vidyasagar Group of Colleges will not be liable for late receiving of any quotation. The Common Committee of Vidyasagar Group of Colleges has a right to reject any quotation without assigning any reason and the decision will be binding all.

**Important Notes:**

1. Date of Publication of Tender : 10.10.2023
2. Time for Submission : 11.00 am to 4.00 pm (except Holidays)
3. Last date for submission : 17.10.2023 upto 2.00pm
4. Place of Submission : Tender box placed at the first floor in front of room no. 9 of Vidyasagar College (old building) 39, Sankar Ghosh Lane Kolkata-700006
5. Opening of Tender : 17.10.2023 at 2.15 pm

Sd/-  
Convener  
Common Committee  
Vidyasagar Group of Colleges

## Annexure

### Renovation of Physics lab, gents and ladies toilet at Vidyasagar Group of Colleges (Old Building)

Sl. No	Description of Items	Unit	Qty.	Rate (Rs.)	Amount (Rs.)
<b>1</b>	<b>FLOORING</b>				
1.1	Supplying and laying true in level vitrified tiles of approved brand (size not less than 600x600mmx10mm thick) in floor, skirting, treads, risers etc. set in 20mm sand cement mortar (1:4) and 2mm thick cement slurry back side of tiles using cement @ 2.91Kg/Sq.m or using polymerised adhesive (6mm thick layer applied directly over finished floor without any backing course) laid after application slurry using 1.75Kg of cement/Sq.m below mortar only, joints grouted with admixture of white cement and colouring pigment to match with colour of tiles and polishing the tiles using soft and dry cloth upto mirror finish complete including the cost of materials, labour and all other incidental charges complete true to the manufacturer's specification and direction of Engineer.	Sq.M	2.00		
1.2	Supplying, fitting, fixing marble slab/tiles, 15 mm. to 18 mm. thick in dado / wall in 15 mm thick [avg] cement mortar (1:2) including making suitable arrangements to hold the stones properly by brass / copper hooks applying white cement slurry @ 4.4 kg/ sq.m at the back side of marble & pointing in cement mortar (1:2) (1 cement, 2 marble dust) with admixture of pigment matching the stone shades including polishing all complete as per direction of the Engineer-in-charge including cost of materials, labours, scaffolding, staging, curing complete. [White cement, Pigment to be supplied by the Agency]. (a) With Chawk Doongri Area of each slab/tile exceeding 1.00 sq.m (This item to be executed on Specific permission of Superintending Engineer)	Sq.M	4.00		
1.3	Supplying, fitting & fixing 1st class quality <b>Ceramic tiles</b> in walls and floors to match with the existing floor level Set in 20mm sand cement mortar (1:4) and 2mm thick cement slurry back side of tiles using cement @ 2.91kg/Sq.m or using polymerised adhesive laid after application slurry using 1.75 Kg of cement per Sq.m below mortar only, joints grouted with admixture of white cement and colouring pigment to match with colour of tiles /epoxy grout materials of approved make as directed. The rate is inclusive of all materials, labour and all other incidental charges complete true to the manufacturer's specification and direction of EIC.				

i)	<b>Floor</b>				
	With Sand Cement Mortar (1:4) 20 mm thick & 2 mm thick cement slurry at back side of tiles using cement @ 2.91 Kg/Sq.m & joint filling using white cement slurry @ 20kg/Sq.m. a) Area of each tile upto 0.09 Sq.m Coloured decorative .	Sq.M	25.00		
ii)	<b>Wall</b>				
	With Sand Cement Mortar (1:4) 15mm thick and 2mm thick cement slurry at back side of tiles with adhesive. a) Area of each tile upto 0.09 Sq.m Coloured decorative .	Sq.M	64.00		
				<b>TOTAL</b>	
	GST @ 18%				
			<b>Grand Total:</b>		
	(Rupees ..... )				
	Date:	Signature of the Contractor			
	Place:				